

OSBORN SPRAY ADHESIVE 76240

SAFETY DATA SHEET

OSHA HCS (29 CFR 1910.1200)

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Chemical Name	Mixture
CAS No.	Mixture
Trade Name	OSBORN SPRAY ADHESIVE 76240
Product Code	M-5716

Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s)	Adhesive Product
Uses Advised Against	None

Company Identification	Osborn 2350 Salisbury Road North Richmond, IN 47374 USA
------------------------	---

Telephone	(765) 965-5333
Fax	(765) 935-0212
E-Mail (competent person)	marketsupport@osborn.com

Emergency telephone number

Emergency Phone No.	Transportation Emergency: CHEMTREC 24 hr. 1-800-424-9300 / 1 (703) 527-3887 (Collect calls accepted)
---------------------	---

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

OSHA HCS (29 CFR 1910.1200)

Flam. Aerosol 1; Liquefied gas; Eye Irrit. 2; Skin Irrit. 2; Repr. 2; STOT SE 3; STOT RE 2; Asp. Tox. 1

Label elements

Hazard Symbol



DANGER

Signal word(s)

Hazard Statement(s)

Extremely flammable aerosol.
Contains gas under pressure; may explode if heated.
Causes serious eye irritation.
Causes skin irritation.
Suspected of damaging fertility or the unborn child.
May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure:
Central Nervous System, Route: Inhalation
May be fatal if swallowed and enters airways.

OSBORN SPRAY ADHESIVE 76240

Precautionary Statement(s)

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.

Avoid breathing spray.

Wear protective gloves/eye protection.

Wash hands and exposed skin after use.

Use only outdoors or in a well-ventilated area.

Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F.

Other hazards

None

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredient(s)	% wt. *	CAS No.	Hazard classification
Dimethyl ether	35 - 45	115-10-6	Flam. Gas 1; H220 Liquefied gas; H280
n-Hexane	15 - 25	110-54-3	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Repr. 2; H361 Skin Irrit. 2; H315 STOT SE 3; H336 STOT RE 2; H373
Acetone	20 - 25	67-64-1	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336
Non-hazardous resins, polymers, and other additives	< 15	-----	Not classified as dangerous for supply/use.

Additional Information - None

* The exact percentage withheld as a trade secret in accordance with 29 CFR 1910.1200.

SECTION 4: FIRST AID MEASURES



Description of first aid measures

Inhalation

Remove person to fresh air and keep comfortable for breathing. If breathing is labored, administer oxygen. If symptoms develop, obtain medical attention.

Skin Contact

Wash affected skin with soap and water. If skin irritation occurs, get medical advice/attention. Take off contaminated clothing and wash it before reuse.

Eye Contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if eye irritation develops or persists.

Ingestion

Do not give anything by mouth to an unconscious person. Do NOT induce vomiting. Get medical attention immediately.

Most important symptoms and effects, both acute and delayed

Aspiration of droplets may cause pulmonary oedema.

OSBORN SPRAY ADHESIVE 76240

Indication of any immediate medical attention and special treatment needed

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

- Suitable Extinguishing Media
- Unsuitable Extinguishing Media

Extinguish with carbon dioxide, dry chemical, foam or water spray. Do not use water jet.

Special hazards arising from the substance or mixture

Highly flammable vapor (flash point below 23°C).

Advice for fire-fighters

A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Keep containers cool by spraying with water if exposed to fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Eliminate sources of ignition. Avoid contact with skin and eyes. Avoid breathing spray. Wear protective gloves/eye protection.

Environmental precautions

Prevent liquid entering sewers, basements and work pits.

Methods and material for containment and cleaning up

Cover spills with inert absorbent material. Transfer to a container for disposal or recovery.

Reference to other sections

None

Additional Information

None

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling

Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Avoid contact with skin and eyes. Use product in a well-ventilated area only. Avoid breathing spray.

Conditions for safe storage, including any incompatibilities

-Storage temperature

Keep in a cool, well ventilated place. Protect from sunlight. Store at temperatures not exceeding 50 °C / 122 °F. Keep container tightly closed.

-Incompatible materials

This product should be stored away from sources of strong heat and oxidizing chemicals. Also avoid: acids, bases, reducing agents, peroxides, amines, ammonia, chlorine and halogens.

Specific end use(s)

Adhesive Product

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

SUBSTANCE.	CAS No.	(8hr TWA)		(STEL)		Note:
		PEL (OSHA)	TLV (ACGIH)	PEL (OSHA)	TLV (ACGIH)	
Hexane	110-54-3	500 ppm	50 ppm*	-----	-----	*Skin
Acetone	67-64-1	1000	500	-----	750	^NIC

^NIC = Notice of Intended Changes (ACGIH®);

Recommended monitoring method

NIOSH 1500 (hydrocarbons, B.P. 36 - 126 °C); NIOSH 1300 (Ketones I).

Exposure controls

Appropriate engineering controls

Provide adequate ventilation to ensure that the occupational exposure limit is not exceeded.

OSBORN SPRAY ADHESIVE 76240

Personal protection equipment

Eye/face protection



Wear protective eyewear (goggles, face shield, or safety glasses).

Skin protection (Hand protection/ Other)



Wear suitable gloves if prolonged skin contact is likely. Check with protective equipment manufacturer's data.

Respiratory protection



Normally no personal respiratory protection is necessary. In case of insufficient ventilation, wear suitable respiratory equipment. Check with protective equipment manufacturer's data.

Thermal hazards

Not normally required. Use gloves with insulation for thermal protection, when needed.

Environmental Exposure Controls

None known

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Aerosol spray
Color.	Clear
Odor	Pleasant
Odor Threshold (ppm)	Not available
pH (Value)	Not available
Melting Point (°C) / Freezing Point (°C)	Not available
Boiling point/boiling range (°C):	Not available
Flash Point (°C)	-41 °C (Dimethyl ether)
Evaporation Rate	Not available
Flammability (solid, gas)	Flammable aerosol.
Explosive Limit Ranges	3.4% - 18% v/v (Dimethyl ether)
Vapor pressure (Pascal)	42.7×10^4 (Dimethyl ether)
Vapor Density (Air=1)	1.6 (Dimethyl ether)
Density (g/ml)	Not available
Solubility (Water)	Not available
Solubility (Other)	Not available
Partition Coefficient (n-Octanol/water)	Not available
Auto Ignition Point (°C)	Not available
Decomposition Temperature (°C)	Not available
Kinematic Viscosity (cSt)	Not available
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.

Other information

None

SECTION 10: STABILITY AND REACTIVITY

Reactivity

Stable under normal conditions.

Chemical stability

Stable.

Possibility of hazardous reactions

None anticipated.

Conditions to avoid

Avoid contact with heat and ignition sources.

Incompatible materials

This product should be stored away from sources of strong heat and oxidizing chemicals. Also avoid: acids, bases, reducing agents, peroxides, amines, ammonia, chlorine and halogens.

Hazardous decomposition product(s)

Forms carbon oxides under fire conditions.

OSBORN SPRAY ADHESIVE 76240

SECTION 11: TOXICOLOGICAL INFORMATION

Exposure routes: Inhalation, Skin Contact, Eye Contact

Information on toxicological effects

Dimethyl ether (CAS# 115-10-6):

Acute toxicity	Inhalation: LC50 : 164000 ppm (gas), 4-hr. rat
Irritation/Corrosivity	Not to be expected
Sensitization	Not to be expected
Repeated dose toxicity	Not to be expected
Carcinogenicity	It is unlikely to present a carcinogenic hazard to man.

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.

Mutagenicity	Not to be expected
Reproductive toxicity	Not to be expected

n-Hexane (CAS No. 110-54-3):

Acute toxicity	Oral: LD50 ≈16 g/kg-bw (May be fatal if swallowed and enters airways.) Dermal: LD50 >2 g/kg-bw. rabbit Inhalation: LC50 > 17600 mg/m3 (Vapor), 24-hr. rat (May cause drowsiness or dizziness.)
Irritation/Corrosivity	Causes skin irritation. Repeated exposure may cause skin dryness or cracking.
Sensitization	It is not a skin sensitizer.
Repeated dose toxicity	LOAEL: 37973 mg/kg (101 days, oral, rat, CNS effects) NOAEL: 1135 mg/kg (101 days, oral, rat, CNS effects) NOAEC: 1760 mg/m3 (90 day, inhal., female mice, nasal lesions) LOAEC: 3000 ppm (12 hr a day for 16 weeks, inhal., rat, CNS effects)
Carcinogenicity (By analogy with similar materials)	NOEL: 31736 mg/m3 (2 years, inhal. Oncogenic effects)

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.

Mutagenicity	There is no evidence of mutagenic potential.
Reproductive toxicity	Studies in animals have shown that repeated exposures produce adverse reproductive effects.

Acetone (CAS No. 67-64-1):

Acute toxicity	Oral LD50 = 5800 mg/kg (rat) Dermal LD50 >15800 mg/kg (rabbit) Inhalation LC50 76 mg/L (4 hour(s)) (rat) - Vapours may cause drowsiness and dizziness.
Irritation / Corrosivity	Causes serious eye irritation. Repeated exposure may cause skin dryness or cracking.
Sensitisation	It is not a skin sensitiser.
Repeated dose toxicity	Oral NOAEL = 900 mg/kg/day (rat) (90-days) Inhalation NOAEL ≥ 19,000 ppm (rat)
Carcinogenicity	It is unlikely to present a carcinogenic hazard to man.

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.

Mutagenicity	Negative
Toxicity for reproduction	Negative
Other information	None known.

OSBORN SPRAY ADHESIVE 76240

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Dimethyl ether (CAS# 115-10-6):

Short term (calculated/estimated)

LC50: 1783.04 mg/l (96 hr) (fish)
LC50: 755.549 mg/l (48hr) (aquatic invertebrates)
EC50: 154.917 mg/l (96 hr) (algae)
Not available.

Long Term

n-Hexane (CAS# 110-54-3):

Short term

LC50 (96 hour): >1000 µg/L (*Oryzias latipes*)
LC50 (48 hour): 45 mmol/m3 (*Daphnia magna*, mortality)
EC50 (96 hour): 2.66% (*C. pyreniodosa*)

Long Term

NOELR (28 days) 2.8 mg/l (*Fish*) QSAR
NOELR (21 days): 4.88 mg/l (*Daphnia magna*) QSAR
NOEL (96 hour) 2.077 mg/l (Algae) QSAR

Acetone (CAS No. 67-64-1):

Short term

LC50 (96 hour): 5,540 mg/l (Rainbow Trout (*Oncorhynchus mykiss*))
LC50 (96 hour): 8,300 mg/l (Bluegill Sunfish (*Lepomis macrochirus*))
LC50 (48 hour(s)): 12,600 – 12,700 mg/l (*Daphnia magna*)
EC50 (14 d): 3,020 mg/l (Algae (*Chlorella pyrenoidosa*))
EC50 (15 min): 14,500 mg/l (Bacteria (*Photobacterium phosphoreum*))

Long Term

Not available.

Persistence and degradability

Readily biodegradable.

Bioaccumulative potential

Not available.

Mobility in soil

Not available.

Results of PBT and vPvB assessment

Not available.

Other adverse effects

None known.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal should be in accordance with local, state or national legislation. Consult an accredited waste disposal contractor or the local authority for advice.

SECTION 14: TRANSPORT INFORMATION

	<u>U.S. DOT</u>	<u>Sea transport (IMDG)</u>	<u>Air transport (ICAO/IATA)</u>
UN number	1950	1950	1950
Proper Shipping Name	Aerosols, flammable	Aerosols, flammable	Aerosols, flammable
Transport hazard class(es)	2.1	2.1	2.1
Packing group	Not applicable	Not applicable	Not applicable
Environmental hazards	None assigned	None assigned	None assigned
Special precautions for user	None assigned	None assigned	None assigned

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture:

TSCA (Toxic Substance Control Act) - Inventory Status: All components listed or polymer exempt.

OSBORN SPRAY ADHESIVE 76240

Designated Hazardous Substances and Reportable Quantities (40 CFR 302.4):

Chemical Name	CAS No.	Typical %wt.	RQ (Pounds)
n-Hexane	110-54-3	15-25	5000
Acetone	67-64-1	20-25	5000

SARA 311/312 - Hazard Categories:

☒ Fire ☒ Sudden Release ☐ Reactivity ☒ Immediate (acute) ☒ Chronic (delayed)

SARA 313 - Toxic Chemicals (40 CFR 372):

Chemical Name	CAS No.	Typical %wt.
n-Hexane	110-54-3	15-25

SARA 302 - Extremely Hazardous Substances(40 CFR 355):

Chemical Name	CAS No.	Typical %wt.	TPQ (pounds)
None	----	----	----

California Proposition 65 List:

Chemical Name	CAS No.	Type of Toxicity
None	----	----

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16.

Date of preparation: May 25, 2015

Hazard Statement(s) and Risk Phrases Listed in: SECTION 2:/ SECTION 3:

Hazard Statement(s)

- H220: Extremely flammable gas.
- H225: Highly flammable liquid and vapor.
- H280: Contains gas under pressure; may explode if heated.
- H304: May be fatal if swallowed and enters airways.
- H315: Causes skin irritation.
- H319: Causes serious eye irritation.
- H336: May cause drowsiness or dizziness.
- H361: Suspected of damaging fertility or the unborn child.
- H373: May cause damage to organs through prolonged or repeated exposure.

Training advice: None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.